

Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RM 838
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Detergent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Alfred Kärcher SE & Co. KG Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden

Postfach 160

D - 71349 Winnenden

*Tel.:* +49-7195-14-0 *Fax:* +49-7195-14-2212

www.karcher.com

· Further information obtainable from:

Department PCD-D Tel.: +49-7195-14-2548 Fax: +49-7195-14-3164 safetydata@karcher.com

· 1.4 Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Met. Corr.1

H290 May be corrosive to metals.

Skin Corr. 1A

H314 Causes severe skin burns and eye damage.

Eye Dam. 1

H318 Causes serious eye damage.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



(Contd. of page 1)

Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

#### · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labelling:

2-aminoethanol

#### · Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

### · Additional information:

Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

EC number: 931-292-6	Amines, C12-14-alkyldimethyl, N-oxides	5-<10%
Reg.nr.: 01-2119490061-47-0008	Eye Dam. 1, H318; � Aquatic Acute 1, H400; Aquatic Chronic 2, H411; � Acute Tox. 4, H302; Skin Irrit. 2, H315	
CAS: 141-43-5	2-aminoethanol	2.5-<59
EINECS: 205-483-3	♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302;	
Index number: 603-030-00-8	Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE	
Reg.nr.: 01-2119486455-28-xxxx	3, H335; Aquatic Chronic 3, H412	
CAS: 1310-73-2	sodium hydroxide	0.5-<29
EINECS: 215-185-5	Met. Corr.1, H290; Skin Corr. 1A, H314	
Index number: 011-002-00-6		
Reg.nr.: 01-2119457892-27-xxxx		

Contd. on page 3



Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

CAS: 5989-27-5	(R)-p-mentha-1,8-diene	(Contd. of page 2 0.1-<0.25%
EINECS: 227-813-5 Index number: 601-029-00-7	Flam. Liq. 3, H226; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	
· Regulation (EC) No 648/2004 (	on detergents / Labelling for contents	•
amphoteric surfactants		≥5 - <15%
perfumes (LIMONENE)		
· Additional information For the	wording of the listed hazard phrases refer to section 10	б.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Immediately remove any clothing soiled by the product.
- · After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing

Rinse out mouth and then drink plenty of water.

 $Do \ not \ induce \ vomiting; \ call \ for \ medical \ help \ immediately.$ 

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with full jet.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- $\cdot \textit{Additional information}$

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

(Contd. of page 3)

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with eyes and skin.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility:

Do not store together with acids.

Keep away from food, beverages and feed.

- · Further information about storage conditions: Keep receptacle tightly sealed.
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

. Ingredients	with limit	values th	at roauiro	monitoring	at the workplace:

#### 141-43-5 2-aminoethanol

*IOELV* Short-term value: 7.6 mg/m³, 3 ppm

Long-term value: 2.5 mg/m³, 1 ppm

Skin

#### · DNELs

#### 308062-28-4 (C12-C18)Alkyl dimethylamine oxide

Dermal DNEL 11 mg/kg\*d (employee)
Inhalative DNEL 15.5 mg/m3 (Employee)

(Contd. on page 5)



Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

		(Contd. of page 4)	
141-43-5 2	141-43-5 2-aminoethanol		
Oral	DNEL	3.75 mg/kg*d (consumer)	
Dermal	DNEL	1 mg/kg*d (employee)	
Inhalative	DNEL	3.3 mg/m3 (employee)	
		2 mg/m3 (consumer)	

- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

· Protection of hands:



Protective gloves.

- · Material of gloves Butyl rubber, BR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles (EN 166)

#### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Orange
Odour: citrus-like
Odour threshold: Not determined.

• pH-value at 20 °C: 13.3
 • pH-value 1 %: 10.5

(Contd. on page 6)



Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

	(Contd. of pag
· pH 1 % dem.	11.6
· Change in condition	
Melting point/freezing point:	-10 °C
Initial boiling point and boiling range	:: >100 °C
· Flash point:	Not applicable
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	not applicable
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
Density at 20 °C:	1.076 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
dynamic at 20 °C:	34 mPas
kinematic:	Not determined.
· Solvent content:	
Organic solvents:	5.0 %
VOC (EC)	5.01 %
Solids content:	31.5 %
· 9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity corresponds to 10.3
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Strong exothermic reaction with acids

Reacts with light alloys to form hydrogen

Corrodes aluminium

(Contd. on page 7)



Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

(Contd. of page 6)

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Not compatible with alkali-sensitive substances like Sn, Zn, Al and paintings.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 1	· LD/LC50 values relevant for classification:		
308062-28	308062-28-4 (C12-C18)Alkyl dimethylamine oxide		
Oral	LD50	1,064 mg/kg (Rat)	
Inhalative	LC50	3,600 mg/kg (Rat)	
141-43-5 2	141-43-5 2-aminoethanol		
Oral	LD50	1,515 mg/kg (Rat) (OECD 401)	
Dermal	LD50	1,025 mg/kg (Rat)	
Inhalative	LC50/6h	>1.3 mg/l (Rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12.1 Toxicit	y	
Aquatic toxi	city:	
308062-28-4	(C12-C18)Alkyl dimethylamine oxide	
LC50	2.67 mg/l (fish)	
141-43-5 2-0	minoethanol	
LC50/96 h	>100 mg/l (Cyprinus carpio) (OECD 203)	
	329 mg/l (Lepomis macrochirus)	
EC50/48 h	65 mg/l (Daphnia magna)	
1310-73-2 sc	odium hydroxide	
LC50/96 h	125 mg/l (Gambusia affinis)	

EU



Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

(Contd. of page 7)

EC50/48 h 76 mg/l (Daphnia magna)

EC50/15 min | 22 mg/l (Photobacterium phosphoreum)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · COD-value: 611000 mg/l
- · General notes:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

The contained organic complexing agents reach a DOC-elimination grade of 80% (corresponding to No. 406 of Annex "Analytic and measuring methods") and with this meet the tightened demands of Annex 49 of the revised Direction on liqid waste.

The product does not contain organically bounded halogens (AOX-free).

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

· European waste catalogue

07 06 01\* aqueous washing liquids and mother liquors

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.
- · Recommended cleansing agents: Water, if necessary together with cleaning agents.

EH-

(Contd. on page 9)



Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

(Contd. of page 8)

14.1 UN-Number	
ADR, IMDG, IATA	UN1760
14.2 UN proper shipping name	
ADR	1760 CORROSIVE LIQUID, N.O.S. (SODIU
HAD C TATE	HYDROXIDE, ETHANOLAMINE)
IMDG, IATA	CORROSIVE LIQUID, N.O.S. (SODIU HYDROXIDE, ETHANOLAMINE)
14.3 Transport hazard class(es)	
ADR	
Class	8 (C9) Corrosive substances.
Label	8
IMDG, IATA	
A	
530	
8	
Class	8 Corrosive substances.
Label	8
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	88
EMS Number:	F- $A$ , $S$ - $B$
Segregation groups	Alkalis
Stowage Category	B
Stowage Code	SW2 Clear of living quarters.
14.7 Transport in bulk according to Annex II	v
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
Transport/Additional information: ADR	



Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

	(Contd. of page 9
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500
	ml
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500
	ml
· UN ''Model Regulation'':	UN 1760 CORROSIVE LIQUID, N.O.S. (SODIUM
· ·	HYDROXIDE, ETHANOLAMINE), 8, II

#### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. A product information sheet can be provided if requested.

· Relevant phrases

H226 Flammable liquid and vapour.

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 11)



Printing date 08.03.2019 Version number 3 Revision: 13.06.2017

Trade name: RM 838

(Contd. of page 10)

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: PCD-D

· Contact:

Department PCD-D Tel.: +49-7195-14-2548 Fax: +49-7195-14-3164 safetydata@karcher.com

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

 $Flam.\ Liq.\ 3:\ Flammable\ liquids-Category\ 3$ 

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1B: Skin corrosion/irritation – Category 11

Skin Irrit. 2: Skin corrosion/irritation – Category 2

 $\label{eq:condition} \textit{Eye Dam. 1: Serious eye damage/eye irritation} - \textit{Category 1}$ 

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* \* Data compared to the previous version altered.

0.011-324.0

RM 838/4

2.138

EH